

# C50

## CAMERA HEAD



DEPLOYMENT RANGE:

**DN100 TO DN300 (4"-12")**

RESOLUTION: 1920 X 1080 PX (**FULL HD**)

**ZOOM:** 4X (DIGITAL)

TILT RANGE: -135° TO 135°

ENDLESS ROTATION

PHOTOSENSITIVITY: 0,001 LUX (F1,8, AGC)

BRIGHT ILLUMINATION USING POWER LEDS

TWO-POINT LASER MEASURING FUNCTION

DIMENSIONS: 58 X 97 MM (2.3" X 3,8")

WEIGHT: **0.6 KG (1.3 LBS)**

PRESSURE-TIGHT UP TO **1 BAR**

**IP68** (DUST- AND WATERPROOF)

ROTATION AND TILT SENSOR

INNER TEMPERATURE AND PRESSURE SENSOR

OPERATING TEMPERATURE:

0 °C TO 40 °C (32°F TO 104°F)

STORAGE TEMPERATURE:

-20 °C TO 60 °C (-4°F TO 140°F)

1080p

FULLHD



INFORMATION | **ONLINE**



## OUR SMALLEST CRAWLER CAMERA.

CAMERA HEAD FOR USE  
WITH C-SERIES CRAWLERS (CRC90/CRC130)

**NSP3CT**<sup>PRO</sup>