

C90

CAMERA HEAD



DEPLOYMENT RANGE:

DN100 TO DN1000 (4" TO 40")

RESOLUTION: 1920 X 1080 PX (**FULL HD**)

ZOOM: 10X (OPTICAL)

TILT RANGE: -135° TO 135°

ENDLESS ROTATION

PHOTOSENSITIVITY: 0.05 LUX

AUTOMATIC / MANUAL FOCUS

BRIGHT ILLUMINATION USING POWER LEDS

TWO-POINT LASER MEASURING FUNCTION

DIMENSIONS: 92 X 168 MM (3.6" X 6.6")

WEIGHT: **1.6 KG (3.5 LBS)**

PRESSURE-TIGHT UP TO **1 BAR**

IP68 (DUST- AND WATERPROOF)

ROTATION AND TILT SENSOR

INNER TEMPERATURE AND PRESSURE SENSOR

OPERATING TEMPERATURE:

0 °C TO 40 °C (32°F TO 104°F)

STORAGE TEMPERATURE:

-20 °C TO 60 °C (-4°F TO 140°F)



1080p

FULLHD

INFORMATION | **ONLINE**



ALWAYS A
CLEAR VIEW AT THINGS.

CAMERA HEAD FOR USE
WITH C-SERIES CRAWLERS (CRC90/CRC130)

NSP3CT^{PRO}