CR\\\\\130

NSP3CT.PR0 GMBH // 2025.10.29

CRAWLER |



DEPLOYMENT RANGE: **DN150 TO DN1000**

ELECTRONIC LIFTER

FULL HD BACKEYE CAMERA (PICTURE-IN-PICTURE) DIMENSIONS: 430 X 106 X 99 MM WEIGHT INCL. PLUG: 10.5 KG

6-WHEEL-DRIVE

FASTLOC SYSTEM FOR

QUICK WHEEL CHANGES (OPTIONAL)

PRESSURE-TIGHT UP TO 1 BAR

LOCATION: 512 Hz, 640 Hz, 33 kHz

IP68 (DUST- AND WATERPROOF)

POWER SUPPLY VIA CABLE DRUM

TILT SENSOR, INCLINATION MEASUREMENT INNER TEMPERATURE AND PRESSURE SENSOR OPERATING TEMPERATURE: 0 °C TO 40 °

STORAGE TEMPERATURE: -20 °C TO 60 °C



CRC130 RUBBER WHEEL SET 65MM (SCREW-ON)

FILLING ADAPTER







INFORMATION | ONLINE



HIGH TECH AT LOW COSTS.

FOR USE WITH C-SERIES FULL HD CAMERA HEADS

AND CABLE DRUMS FROM 100 TO 300 METERS FOR DN150 TO DN1000

