

# CRC130

NSP3CT.PRO GMBH // 2025.10.29

## CRAWLER



DEPLOYMENT RANGE:  
**DN150 TO DN1000 (6" TO 40")**

### ELECTRONIC LIFTER

**FULL HD** BACKEYE CAMERA  
 (PICTURE-IN-PICTURE)

DIMENSIONS:  
 430 X 106 X 99 MM (17" X 4.2" X 4")

WEIGHT INCL. PLUG: **10.5 KG (23.2 LBS)**

### 6-WHEEL-DRIVE

FASTLOC SYSTEM FOR  
**QUICK WHEEL CHANGES** (OPTIONAL)

PRESSURE-TIGHT UP TO **1 BAR**

**LOCATION:** 512 Hz, 640 Hz, 33 kHz

**IP68** (DUST- AND WATERPROOF)

POWER SUPPLY VIA CABLE DRUM

TILT SENSOR, INCLINATION MEASUREMENT

INNER TEMPERATURE AND PRESSURE SENSOR

OPERATING TEMPERATURE:  
 0 °C TO 40 °C (32°F TO 104°F)

STORAGE TEMPERATURE:  
 -20 °C TO 60 °C (-4°F TO 140°F)

## ACCESSORIES

RUBBER SCREW-ON WHEEL SET 65MM (2.5")

FILLING ADAPTER



CAMERA HEAD NOT INCLUDED



INFORMATION | **ONLINE**



# HIGH TECH AT LOW COSTS.

FOR USE WITH C-SERIES FULL HD CAMERA HEADS AND CABLE DRUMS

# NSP3CT<sup>PRO</sup>