oxdot



NSP3CT.PR0 GMBH // 2025.10.29

## CRAWLER



DEPLOYMENT RANGE: **DN100 TO DN300** 

FULL HD BACKEYE CAMERA (PICTURE-IN-PICTURE) DIMENSIONS: 346 X 65 X 68 MM WEIGHT INCL. PLUG: 4.9 KG

6-WHEEL-DRIVE

FASTLOC SYSTEM FOR

**QUICK WHEEL CHANGES (OPTIONAL)** 

PRESSURE-TIGHT UP TO 1 BAR LOCATION: 512 Hz, 640 Hz, 33 kHz IP68 (DUST- AND WATERPROOF) POWER SUPPLY VIA CABLE DRUM

TILT SENSOR, INCLINATION MEASUREMENT INNER TEMPERATURE AND PRESSURE SENSOR OPERATING TEMPERATURE: 0 °C TO 40 ° STORAGE TEMPERATURE: -20 °C TO 60 °C



CRC90 RUBBER WHEEL SET 55MM (SCREW-ON) FILLING ADAPTER





INFORMATION | **ONLINE** 



## **OUR SMALLEST** CRAWLER.

FOR USE WITH C-SERIES FULL HD CAMERA HEADS

AND CABLE DRUMS FROM 100 TO 300 METERS FOR DN100 TO DN300

