



## CONTROL UNIT

TWO **PRECISE 3-AXIS JOYSTICKS**  
(X/Y/Z) WITH TWO BUTTONS EACH

ADDITIONALLY TWO  
**CONFIGURABLE** BUTTONS PER UNIT

**ROTARY KNOB** WITH INTEGRATED  
**DISPLAY** ON THE RIGHT UNIT

INTEGRATED **USB HUB**

INTEGRATED **EMERGENCY STOP**

**OPTIONAL MOUNTING POSSIBILITY**  
ON DESK SURFACE IN VEHICLE

**ERGONOMIC**, ANGLED HOUSING DESIGN

MATERIAL: ABS, RUBBER, ALUMINIUM

**IP40** (PROTECTED AGAINST INTRUSION FROM  
SOLID FOREIGN OBJECTS)

**CONNECTIONS:** USB-A 2.0

POWER SUPPLY: VIA USB

DIMENSIONS: 185 MM × 135 MM × 90 MM  
(INCL. JOYSTICK) PER UNIT

WEIGHT: 1.2 KG

OPERATING TEMPERATURE: 0 °C TO 40 °C

STORAGE TEMPERATURE: -20 °C TO 60 °C

**COMPATIBLE** WITH HMX



INFORMATION | **ONLINE**



# YOUR STATIONARY COMMAND CENTRE.

ERGONOMIC IN-VEHICLE CONTROL SYSTEM FOR SIMULTANEOUS  
CONTROL OF CRAWLERS AND CAMERA SYSTEMS OF THE C-SERIES

**NSP3CT**<sup>PRO</sup>