

TW60

TWO PUSH CAMERA



DEPLOYMENT RANGE FROM DN50

SELF-LEVELLING 40MM
C40SL AXIAL CAMERA HEAD

FULL HD CAMERA 1080P/30 (IP68)

SAPPHIRE GLASS LENS

PRESSURE-RESISTANT UP TO 1 BAR

60M FLEXIBLE FIBRE GLASS PUSH ROD

IPX6 (PROTECTED AGAINST STRONG WATER JETS)

LOCATION (512 HZ, 640 HZ AND 33 KHZ)

HIGH-PRECISION **METRE COUNTER**

CONNECTIVITY: WIFI
(BLUETOOTH, 4G/5G READY)

4 HRS LI-ION BATTERY

DIMENSIONS: 576 × 300 × 780 MM

EXTREMELY LIGHTWEIGHT CONSTRUCTION <20 KG

OPERATION **UPRIGHT OR LYING** POSSIBLE

CONTROL VIA HMX OR ANDROID APP

OTA UPDATE FUNCTION

ONLINE OPERATING INSTRUCTIONS



INFORMATION | **ONLINE**



THE EVOLUTION OF THE PUSH CAMERA.

MODULAR FULL-HD PUSH CAMERA WITH 60 M PUSH ROD
FOR PROFESSIONAL DEPLOYMENTS **FROM DN50**

NSP3CT^{PRO}